

Offgridtec® Batterieverbindingkabel – M10 Terminal beidseitig

Eigenschaften

- ❖ **Hochwertiges Batterieanschlusskabel:** Die M10 Schraubterminals sind aus vernickeltem Kupfer gefertigt und dadurch besonders korrosionsbeständig. Die Leiter bestehen aus leitfähigem Kupfer ummantelt mit hochwertigem PVC.
- ❖ **Vielseitig einsetzbar:** Die Kabel eignen sich perfekt, um eine Batterie mit M10 Rundpolen mit einem Gerät, welches ebenfalls über ein M10 Schraubterminal verfügt, und den entsprechenden Querschnitt aufnehmen kann.
- ❖ **Robust und langlebig:** Die Offgridtec Batterieverbindingkabel sind für die Verlegung in trockenen und feuchten Räumen sowie auch in Fahrzeugen konzipiert. Sie eignen sich ideal für Anwendungen mit mittlerer mechanischer Beanspruchung, sind Öl, Kälte und UV-beständig sowie flammwidrig.



Erhältliche Varianten

- ❖ **Länge:** 1m und 2m
- ❖ **Leitungsquerschnitt:** 25mm², 35mm² und 50mm²

Querschnitt	Länge	Artikelnummer	EAN	OD (single copper OD)	copper wire
25mm ²	1m	8-01-010665	4250983254761	10.3mm ±0.15 (0.25)	504.00
25mm ²	2m	8-01-010660	4260737987791	10.3mm ±0.15 (0.25)	504.00
35mm ²	1m	8-01-010670	4250983254778	11.8mm ±0.15 (0.25)	707.00
35mm ²	2m	8-01-010675	4250983254785	11.8mm ±0.15 (0.25)	707.00
50mm ²	1m	8-01-010685	4250983254808	14.3mm ±0.15 (0.25)	1007.00
50mm ²	2m	8-01-010695	4250983254822	14.3mm ±0.15 (0.25)	1007.00

Material	
Mantel	PVC
Leiter	Kupferdraht
Terminal/Ose	vernickeltes Kupfer



Über uns
Offgridtec GmbH
Im Gewerbepark 11
84307 Eggenfelden

Kontakt
☎ +49 8721 91994-00
✉ info@offgridtec.com
🌐 www.offgridtec.com



Offgridtec® Battery Connection Cable – M10 terminal on both ends

Characteristics

- ❖ **High Quality:** The M10 terminals are made of nickel-plated copper, making them highly corrosion resistant. The conductors are made of conductive copper coated with high-quality PVC.
- ❖ **Usability:** The cables are perfect to connect a battery with M10 round terminals to a device that also has an M10 screw terminal and can accommodate the corresponding cross-section.
- ❖ **Durability:** The battery connection cables are designed for installation in dry and humid areas as well as vehicles. They are flame retardant, oil, cold, UV resistant and ideal for applications with moderate mechanical stress.



Available variations

- ❖ **Length:** 1m and 2m
- ❖ **Conductor Cross-Section:** 25mm², 35mm² and 50mm²



cross-section	length	article	EAN	OD (single copper OD)	copper wire
25mm ²	1m	8-01-010665	4250983254761	10.3mm ±0.15 (0.25)	504.00
25mm ²	2m	8-01-010660	4260737987791	10.3mm ±0.15 (0.25)	504.00
35mm ²	1m	8-01-010670	4250983254778	11.8mm ±0.15 (0.25)	707.00
35mm ²	2m	8-01-010675	4250983254785	11.8mm ±0.15 (0.25)	707.00
50mm ²	1m	8-01-010685	4250983254808	14.3mm ±0.15 (0.25)	1007.00
50mm ²	2m	8-01-010695	4250983254822	14.3mm ±0.15 (0.25)	1007.00

material	
jacket	PVC
conductor	copper wire
terminal	plated copper



About us
Offgridtec GmbH
Im Gewerbepark 11
84307 Eggenfelden

Contact
+49 8721 91994-00
info@offgridtec.com
www.offgridtec.com

